Cat. No. DFI2309

Complex®

Notes

Section 10309 – Manufactured Electric Fireplaces

PART 1 GENERAL

1.1 SECTION INCLUDES

- A. Manufactured electric fireplaces.
- B. Accessories.

1.2 RELATED SECTIONS

A. Section 06100 - Rough Carpentry: Wood framed rough opening and enclosure.

1.3 REFERENCES

- A. UL 1278
- B. CSA C22.2 No. 46-13

1.4 SUBMITTALS

- A. Submit under provisions of Section 01300.
- B. Product Data: Manufacturer's data sheets on each product to be used, including:
 - 1. Preparation instructions and recommendations.
 - 2. Storage and handling requirements and recommendations.
 - 3. Installation methods.
- C. Manufacturer's Certificates: Certify products meet or exceed specified requirements.
- D. Manufacturer's warranty.

1.5 DELIVERY, STORAGE, AND HANDLING

- A. Store products in manufacturer's unopened packaging until ready for installation.
- B. Protect materials from exposure to moisture. Do not deliver until after wet work is complete and dry.

1.6 WARRANTY

A. Provide the manufacturers 1 year limited warranty on electrical components.

PART 2 PRODUCTS

2.1 ACCEPTABLE MANUFACTURERS

- A. Pre-fabricated Electric Fireplace:
 - Base: Dimplex Electric Fireplace Glen Dimplex Americas 1367 Industrial Road Cambridge ON N3H 4W3 1-888-DIMPLEX www.dimplex.com archdesign@dimplex.com

Complex[®]

Cat. No. DFI2309

Notes

Section 10309 – Manufactured Electric Fireplaces

- 2. Substitutions not permitted
- 3. Requests for substitutions will be considered in accordance with provisions of Section 01600.

2.2 ELECTRIC FIREPLACES

A. General:

Β.

- Provide all components and accessories required for a complete, functional unit.
 UL or CSA listed.
- Pre-fabricated Electric Fireplace:
- 1. Base Product:
 - a) Dimplex Plug-in Electric Log Insert
 - b) Model Number: DFI2309
 - 2. Description: 23" Electric Fireplace Insert
 - 3. Dimensions:
 - a) Width: 23-1/4" / 590.5mm
 - b) Height: 19-1/2" / 495.3mm
 - c) Depth: 10-3/4" / 273.0mm
 - 4. Electrical:
 - a) Volts: 120
 - b) Watts: 1,375
 - c) BTUs: 4,695
 - 5. Venting: Non-venting
 - 6. Operation: Flame only, flame and heat
 - 7. Heating: Louver-less, fan-forced circulation
 - 8. Liner: Steel
 - 9. Standard features:
 - a) High-contrast flames feature improved brightness and character
 - a) Powerful fan-forced heating capabilities
 - b) Easy installation plug into any standard household outlet
 - 2. Control options:
 - a) On/Off remote control

PART 2 EXECUTION

2.1 INSPECTION

- A. Do not begin installation until substrates have been properly prepared.
- B. If substrate preparation is the responsibility of another installer, notify Architect of unsatisfactory preparation before proceeding.
- C. Verify proper power supply and fuel source are available.

2.2 PREPARATION

A. Clean surfaces thoroughly prior to installation.

Complex®

Cat. No. DFI2309

Notes

Section 10309 – Manufactured Electric Fireplaces

B. Prepare surfaces using the methods recommended by the manufacturer for achieving the best result for the substrate under the project conditions.

2.3 INSTALLATION

- A. Install in accordance with manufacturer's instructions and requirements of authorities having jurisdiction.
- B. Use manufacturer's guidelines for minimum clearances to combustibles, walls, and finishes.
- C. Anchor all components firmly in position for long life under hard use.
- D. Upon completion of installation, visually inspect all exposed surfaces. Touch up scratches and abrasions with touch up paint recommended by the manufacturer; make imperfections invisible to the unaided eye from a distance of 5 feet (1.5 m).

2.4 PROTECTION

- A. Protect installed products until completion of project.
- B. Touch-up, repair or replace damaged products before Substantial Completion.

END OF SECTION