



| | |
|----------|---|
| Cat. No. | FMG3326F, FMG3326F-LP, FMG3726L, FMG3726L-LP, FMG3726R, FMG3726R-LP, FMG4126B & FMG4126B-LP |
| Notes | |

Section 103107 - Manufactured Gas Fireplaces

Part 1 GENERAL

1.1 SECTION INCLUDES

A.Manufactured Direct Vent Gas Fireplaces.

1.2 RELATED SECTIONS

A.Section 04 27 23 - Cavity Wall Unit Masonry.

B.Section 06 10 00 - Rough Carpentry.

C.Section 09 22 16 - Non-Structural Metal Framing.

D.Section 09 28 13 – Non-combustible Backing Boards

E.Section 10 31 16 - Manufactured Fireplace Forms.

F.Section 22 10 00 - Plumbing Piping.

G.Section 26 05 00 - Common Work Results for Electrical

1.3 REFERENCES

A.ANSI Z21.88 - Vented Gas Fireplace Heaters.

B.ANSI/NFPA 70 - National Electric Code.

C.CSA C22.1 - Canadian Electric

1.4 DESIGN / PERFORMANCE REQUIREMENTS

A.Comply with ANSI Z21.88/CSA 2.33 gas-fired appliances.

B.Direct Vent appliances shall be electrically grounded in accordance with the local codes or, in the absence of local codes, with National Electric code, ANSI/NFPA 70, or the Canadian Electric Code, CSA C22.1 as applicable.

1.5 SUBMITTALS

A.Submit under provisions of Section 01 30 00 - Administrative Requirements.

B.Product Data: Manufacturer's data sheets on each product to be used,



| | |
|----------|---|
| Cat. No. | FMG3326F, FMG3326F-LP, FMG3726L, FMG3726L-LP, FMG3726R, FMG3726R-LP, FMG4126B & FMG4126B-LP |
| Notes | |

Section 103107 - Manufactured Gas Fireplaces

including:

1. Preparation instructions and recommendations.
2. Storage and handling requirements and recommendations.
3. Installation Instructions.
4. Operating Instructions.

C.Manufacturer's Certificates: Certify products meet or exceed specified requirements.

1.6 DELIVERY, STORAGE, AND HANDLING

A.Store products in accordance with the manufacturer's instructions.
Store indoors in manufacturer's unopened packaging until ready for installation.

1.7 WARRANTY

A.Product Lifetime Limited Warranty – reference the Owner’s Manual for complete warranty.

PART 2 PRODUCTS

2.1 ACCEPTABLE MANUFACTURERS

A. Pre-fabricated Gas Vented Fireplace:

1. Base: Glen Dimplex Americas
1367 Industrial Road
Cambridge ON N3H 4W3
1-800-668-6663

www.faberfires.com

2. Substitutions not permitted
3. Requests for substitutions will be considered in accordance with provisions of Section 01600.



Cat. No. FMG3326F, FMG3326F-LP, FMG3726L, FMG3726L-LP, FMG3726R, FMG3726R-LP, FMG4126B & FMG4126B-LP

Notes

Section 103107 - Manufactured Gas Fireplaces

2.2 GAS VENTED FIREPLACES

- A. General:
 - 1. Provide all components and accessories required for a complete, functional unit.
 - 2. UL or CSA listed.
- B. Pre-fabricated Gas Vented Fireplace:
 - 1. Base Product:
 - a) Faber Gas Vented Fireplace
 - b) Model Number: FMG3326F, FMG3326F-LP, FMG3726L, FMG3726L-LP, FMG3726R, FMG3726R-LP, FMG4126B & FMG4126B-LP
 - 2. Description:
 - a) FMG3326F - Front Facing Built-in Natural Gas Firebox
 - b) FMG3326F-LP - Front Facing Built-in Liquid Propane Firebox
 - c) FMG3726L - Left Sided Built-in Natural Gas Firebox
 - d) FMG3726L-LP - Left Sided Built-in Liquid Propane Firebox
 - e) FMG3726R - Right Sided Built-in Natural Gas Firebox
 - f) FMG3726R-LP - Right Sided Built-in Liquid Propane Firebox
 - g) FMG4126B - Bay Built-in Natural Gas Firebox
 - h) FMG4126B-LP - Bay Built-in Liquid Propane Firebox
 - 3. Dimensions:
 - a) Width: 45 3/8" / 1153mm
 - b) Height: 45 1/4" / 1149mm
 - c) Depth: 24 1/2" / 622mm
 - 4. Framing Dimensions: See Owner's Manual
 - a) Dimensions
 - b) Heat Releases and Air Intakes
 - c) Fresh air inlet of 100 in² (6450mm²) is required for optimal performance (Outlet should be included if inlet is listed)
 - d) List Outlet here
 - 5. Electrical:
 - a) Volts: 6V adapter that plugs into a standard 120V



| | |
|----------|---|
| Cat. No. | FMG3326F, FMG3326F-LP, FMG3726L, FMG3726L-LP, FMG3726R, FMG3726R-LP, FMG4126B & FMG4126B-LP |
| Notes | |

Section 103107 - Manufactured Gas Fireplaces

- b) BTUs: 28,000 (MIN) - 42,500(MAX)
- 6. Venting:
 - a) Refer to DuraVent 5/8 venting - www.duravent.com
 - b) [Refer to ICC venting](#)
- 7. Operation: Flame and heat
- 8. Heating: Radiant
- 9. Standard features:
 - a) Logs - Realistic charred log set to maximize the illusion of depth and the appearance of burning firewood. Combine with loose embers for a custom display.
 - b) Light Module - Casts a firelight glow within the media for a truly lifelike effect.
 - c) Rear Wall Steel - Provides a clean, solid dark interior finish to work seamlessly with any décor.
 - d) Remote Control - Sit back and relax, while controlling all fireplace features from the comfort of your chair.
- 10. Control options:
 - a) Direct wired to 120V circuit through the provided 6V DC adaptor or battery operated for normal operation during power outages
 - b) Optional wall switch

PART 2 EXECUTION

2.1 INSPECTION

- A. Do not begin installation until substrates have been properly prepared.
- B. If substrate preparation is the responsibility of another installer, notify Architect of unsatisfactory preparation before proceeding.
- C. Verify proper power supply

2.2 PREPARATION

- A. Clean surfaces thoroughly prior to installation.
- B. Prepare surfaces using the methods recommended by the manufacturer for achieving the best result for the substrate under the project conditions.



| | |
|----------|---|
| Cat. No. | FMG3326F, FMG3326F-LP, FMG3726L, FMG3726L-LP, FMG3726R, FMG3726R-LP, FMG4126B & FMG4126B-LP |
| Notes | |

Section 103107 - Manufactured Gas Fireplaces

2.3 INSTALLATION

- A. Install in accordance with manufacturer's instructions and requirements of authorities having jurisdiction.
- B. Use manufacturer's guidelines for minimum clearances to combustibles, walls, and finishes.
- C. Anchor all components firmly in position per manufacture instructions to maintain life-time limited warranty.

2.4 PROTECTION

- A. Protect installed products until completion of project.

END OF SECTION